

PRODUCT BULLETIN




KNP-SERIES

WIREWOUND RESISTORS
FLAME-PROOF

WILLOW TECHNOLOGIES LTD.
SHAWLANDS COURT, NEWCHAPEL ROAD
LINGFIELD, SURREY, RH7 6BL, ENGLAND
Tel. + 44 (0) 1342 835234 Fax. + 44 (0) 1342 834306
E-mail rob@willow.co.uk
Website <http://www.willow.co.uk>

CERAMIC CORE: 75% ALUMINA
LEAD: TIN PLATED COPPER
CAP: TIN PLATED STEEL CAP
COATING: SILICON
WIRE: Cu-Ni OR Ni-Cr WIRE



Dimensional Correlation

in.	mm
.002	0.05
.020	0.5
.024	0.6
.031	0.8
.059	1.5
.138	3.5
.157	4.0
.217	5.5
.256	6.5
.335	8.5
.354	9.0
.433	11.0
.590	15.0
.709	18.0
.984	25.0
1.063	27.0
1.575	40.0
1.693	43.0



DEDICATION TO EXCELLENCE

TYPE	RATED WATTS	Resistance range
KNP-1/2W	1/2W	0.1 - 240R
KNP-1W	1W	0.1 - 470R
KNP-2W	2W	0.1 - 820R
KNP-3W	3W	0.1 - 820R
KNP-5W	5W	0.1 - 1.3K
KNP-7W	7W	0.1 - 3.3K
KNP-8W	8W	0.1 - 2K
KNP-10W	10W	0.1 - 4.7K

Note: Resistance up to 27 maximum for Non-Inductive type
Lower or higher resistance values other than the list are also available

TYPE	DIMENSIONS (mm)			
	D ±0.5mm	L ±1.5mm	H(MIN)	d ±0.05
KNP-1/2W	3.5	9	25	0.60
KNP-1W	4.0	11	27	0.8
KNP-2W	5.5	15	27	0.8
KNP-3W	5.5	15	27	0.8
KNP-5W	6.5	18	27	0.8
KNP-7W	8.5	25	27	0.8
KNP-8W	8.5	40	27	0.8
KNP-10W	8.5	53	27	0.8


TEMPERATURE COEFFICIENT

-30°C to 200°C ± 300PPM/°C
Resistance Tolerance ± 5


How to Order

Sample Part Number


KNP 1W T300 1RO ± 5%



TEMPERATURE RISE AT 25°C



DERATING CURVE



Characteristics	Condition	Spec.
Resistance Temp. Coeff.	-30°C ~ +200°C	± 300 ppm/°C
Short Time Over Load	5 times of rated wattage for 5 sec.	± 2%
Rate Load	Rate watt 30 min.	± 1%
Voltage Durability	500V AC 1 min.	not changed
Insulation Resistance	500V megger	500 M Ω
Temp Cycle	-30°C ~ 85°C 5 cycles	± 1%
Load Life	40°C 95% RH on-off cycle 500 hrs.	± 5%
Moisture-proof Load Life	40°C 95% RH on-off cycle 500 hrs.	± 3%
Incombustibility	6 times of rated wattage for 5 min.	not flamed

PACKAGING: TAPE AND REEL
 PIECES PER REEL: KNP 1/2W AND 1W 2500
 KNP 2W, 3W AND 5W 1000
 KNP 7W 500
 BULK: KNP 8W AND 10W 100