

NS-15/V2 Dual Axis Inclinometer

With Analog Output



Applications

Zero point detection •

 Aligning and level control

Angle

Advantages

Wide range of application

 Low vibration sensitivity


• Low price

Pinout



1	+Ub	Supply Voltage
2	GND	Ground
3	Erde	Earth
4	GNDx	Ground for analog output Ux
5	GNDy	Ground for analog output Uy
6	Ux	Voltage output Ux
7	Uy	Voltage output Uy


Dimensions (mm)₆₀



The NS-15/V2 dual-axis inclinometer is a member of a family of high performance, competitively priced, single and dual-axis inclinometers. The heart of every HL Planartechnik inclinometer is a small, state-of-the-art, inclination sensor. The sensor, which is comprised of a molded, ceramic case bonded, via a glass sealing process, to a ceramic substrate. Thin film, platinum electrodes are deposited on the substrate. Then the chamber is partially filled with electrolytic fluid and hermetically sealed. The molded, ceramic, sensor housing combined with a precise, planar electrode geometry yields excellent performance and consistent part-to-part uniformity.

The V-type sensors have an internal pre-processor and produce a -/+2 V analog output. They have a compact sturdy design and a whole range of uses are possible thanks to the possibility of many different external-switching combinations. With their machined, aluminium baseplate and IP 65 housing, they are an ideal choice for a variety of industrial, automotive and aerospace applications.

Diagram (angle vs. output signal)



Specifications

Range:	<i>±</i> 15°
Precision:	0.03°bei -3° +3°
	0.08°bei -10° +10°
Resolution:	0.001°
Temperature stability:	
Zero point:	0.1 ° for 0 ℃ +50 ℃
Sensitivity:	0.3° for 0 ℃ +50 ℃
Analog Output:	-2V (-15°) to +2V (+15°)
Operating temp. Range:	0 ℃+70 ℃
Storage temp. Range:	-40 ℃+ 85 ℃
Supply voltage:	+12 +24 VDC
Current consumption:	~ 9mA
Protection class:	IP 65
Connection:	Connector or Pigtail

HL-Planartechnik GmbH